

### DESCRIPTION:

NEXWAX is a water-based matte to satin wax acrylic co-polymer designed to provide lasting protection to smooth, hard-trowelled interior plasters and decorative concrete finishes of walls and floors.

### FEATURES:

- Abrasion-resistant
- Improves slip-resistance
- Non-yellowing
- Enrich colors & natural luster

### PREPARATION:

The surface to be treated must be dry and unexposed to humidity, free of grease, dirt, and dust. The finish ought to be compressed and smooth for best results.

### APPLICATION:

Use a lamb's wool or a micro-fiber applicator. Two to three thin coats are recommended. Let each coat dry 30 to 60 minutes in-between. Buffing at high speed will elevate luster. Allow 4 hours to cure before foot traffic and servicing. Re-apply as needed. Clean tools with water.

### YEILD:

100SF / 16 oz. per coat. Two to three coats are recommended.

### TECHNICAL:

- VOC = 0 gr./lt.
- Flash Point = n/a
- Flammability = 0

### MAINTENANCE:

The waxed finish should be cleaned with water only or water and white vinegar in wet areas or Pledge Multi-Surface and a soft mop. DO NOT USE aggressive cleaners such as citrus-based products, ammonia, 409/Simple Green bleach cleaners. Abrasive sponges are not recommended. Clean tools with water. Remove coating if needed with standard strippers.